

There is Power Mobility. And then there's

POWERFUL MOBILITY



Royale 3 Cargo

Call **1-800-944-1997** or visit us at www.evrider.com

There is Power Mobility. And then there's **POWERFUL MOBILITY**



Ground Clearance	6" in / 15.3 cm
Length - Overall	62" in / 157.5 cm
Width - Overall	36" in / 92 cm - Golf Tires
Height - Overall	53" in / 135 cm
Height for Transport - Minimum	42.5" in / 108cm - Seat Folded
Lift Platform Requirement	48" in x 30" in
Seat - Width & Depth & Height	32"W x 19" Depth x 20"H
Seat - Cushion Height - Maximum	31" in Floor / 21" in Platform
Turning Radius	49.5" in / 126 cm
Wheelbase for Lifts	62" in / 157.5 cm L
Tire Type	Pneumatic Tires
Rim Type	Aluminum Alloy Rims
Wheelbase	41" in / 105 cm
OEM Spec	Front: 3.00 - 10 Rear: 100 / 80-10
Width - Tire	Front: 3.5" / 9 cm Rear: 6.5" / 17 cm
Diameter-Outside	Front: 16" / 41 cm Rear: 16" / 41 cm
Diameter-Rim	Front: 10" / 25.4 cm Rear: 8" / 20.3 cm

Max PSI	Front: 36 Rear: 24
Weight with Batteries	428 lbs / 195 kgs
Weight without Batteries	324 lbs / 147 kgs
Battery Type (Recommended)	Sealed Lead Acid-AGM // 80Ah / 12V
Brake System	Electromagnetic Disc w/ Emergency Hub
Climbing Angle (Maximum Recommended)	12°
Charger Type	8 amp / Off-Board 120 / 140 Volt / 50/60 Hz
Charging Time	6 - 8 hrs
Controller	200 amp / Dynamic Rhino
*Driving Range	Up to 32 miles / 50 km
Load Capacity	450 lbs / 205 kgs
Motor / Transaxle	1300W / 4100RPM / 1.7HP Rear Wheel Drive / Brush Motor
*Speed - Maximum	9.3 mph / 15 kmh
Basket Type & Weight Capacity (Optional) ***	Wire-Black or Travel Case-Black-Locking Rear & Seat Mounted
Color	Burgundy Red Midnight Black Diamond Silver

Control - Display Type	Digital Tritium Controls: Speed, Time, Temp & Battery Usage
Cup Holder	Optional
Leg Room	18" in / 46 cm
Light Type	Running w/Mirror Mounted Signal blinkers
Seat Type	Bench Style
Seat Features	Adjustable Armrests
Seat Swivel	No
Suspension	Full / Independent Front
Tiller Type	Infinite Adjustment
Throttle Control Type	Thumb or Delta
Turning Speed Safety Switch	Std for Turning

(*) SPECIFICATION PERFORMANCE IS DETERMINED IN THE LABORATORY SETTING BASED ON IDEAL CONDITIONS (MINIMAL FRICTION, NO WIND AND CONTROLLED TEMPERATURE AND PRESSURE WITH AN AVERAGE STANDARD WEIGHT). ACTUAL PERFORMANCE WILL BE DIFFERENT THAN RESULTS OBTAINED DURING LABORATORY TESTING.

(***) OPTIONAL & MOUNTING BRACKET REQUIRED FOR INSTALLATION

Call **1-800-944-1997** or visit us at **www.evrider.com**